



NOTES:

1. ANGLE: 10-DEGREE MINIMUM, 45-DEGREE MAXIMUM. 30-DEGREE IS PREFERRED AND TYPICAL FOR ALL CONNECTIONS.
2. INSTALL RUBBER GASKET PER MANUFACTURER'S RECOMMENDATION.
3. PROVIDE STAINLESS STEEL CLAMPS ON BOTH SIDES OF LATERAL.
4. SADDLE WYE SHALL BE SEALTITE, OR APPROVED EQUAL.
5. CONNECTIONS SHOWN ARE ONLY TO BE USED WHEN CONNECTING TO EXISTING LINES. NEW LINES SHALL HAVE WYES.
6. ALL TIE-INS TO SEWER MAINS MUST BE PERFORMED IN THE PRESENCE OF A DEPARTMENT OF PUBLIC WORKS INSPECTOR. CONTRACTOR SHALL COORDINATE INSPECTION.

APPROVED:

/S/

DIRECTOR OF PUBLIC WORKS

Aug 28, 2006

DATE

CITY OF
SIMI VALLEY

DEPARTMENT OF PUBLIC WORKS

SADDLE CONNECTION
TO MAIN

STANDARD PLAN NO.

SV 40-190

SHEET 1 OF 1